

MINILUFT

Automatic air venting valve for smaller systems, provided with manual locking cams. Vertical discharge. Float operated.

Brass body.
 Float in PP.
 Stainless steel AISI 302 spring.
 Seals in ethylene-propylene elastomer and nitrile elastomer.
 Threaded connection
 M UNI-EN-ISO 228.

- Max operating pressure 10 bar
- Max operating discharge pressure 6 bar
- Max temperature 115°C
- Usable fluid water - water+glycol 30%



Code	Size
2828.03.00	3/8"
2828.04.00	1/2"



MAXIMUM DISCHARGE PRESSURE **6 bar**



Vertical discharge.

VASA

Automatic air venting valve, degasser. Float operated.

Nickel-plated brass body.
 Float and the lever in PP.
 Stainless steel AISI 302 spring.
 Seals in ethylene-propylene elastomer and nitrile elastomer.
 Threaded connection
 M UNI-EN-ISO 228.

- Max operating pressure 6 bar
- Max operating discharge pressure 2,5 bar
- Max temperature 100°C
- Usable fluid water - water+glycol 30%



Code	Size
37.03.60	3/8"
37.04.60	1/2"
37.05.60	3/4"
37.06.60	1"



MAXIMUM DISCHARGE PRESSURE **2,5 bar**



Replaceable float unit.
 Cod. 891.00.00
 See spare parts pricelist.